

**Dow Building Solutions**

Strength Comes Easy

TILE BOND™ ROOF TILE ADHESIVE

There are many choices for installing concrete and clay roof tiles. And for the most part, none of them are ideal ... until now.

TILE BOND™ Roof Tile Adhesive from Dow gives a superior solution for installing roof tile. Not only does it go on fast – it stays strong, even in harsh environments where hurricanes, high winds and temperature extremes put adhesive-applied systems to the test.

Tiles Go on Fast and Easy

TILE BOND™ Roof Tile Adhesive can work on a variety of roof tile jobs, including most low/flat, medium, high and two-piece barrel (cap and pan) profiles. TILE BOND works in both new and re-roof applications. And it's ideal for patch and repair – as well as for specialty applications like ridge, rake, valley and hip installations.

TILE BOND is a single-component polyurethane adhesive that eliminates the problems typically found with other attachment methods like mortar, screws, wire ties and two-component foam systems. There's no equipment to calibrate (as you find in two-component products) – with TILE BOND, you just open the valve and you're ready to go.



roofs

walls

slabs

The Superior Solution

TILE BOND™ Roof Tile Adhesive gives contractors a welcome alternative to traditional attachment methods.

Screws puncture waterproof membranes and the roof deck, leading to leaks. Mortar is heavy, labor-intensive and subject to the effects of freeze-thaw cycles. And two-component systems represent a considerable investment of money, while also requiring continual monitoring of ratios.

By contrast, TILE BOND requires no equipment to apply and protects tiles and other components far better than other methods – while maintaining exceptional adhesive qualities in even the harshest weather.

Convenience and Simplicity

TILE BOND™ Roof Tile Adhesive comes in two convenient sizes. The 23 lb container of TILE BOND is ideal for larger jobs and will adhere up to 750 field tiles. A dispenser is included with each canister that helps you apply it quickly and accurately. The 20 oz can of TILE BOND is ideal for small jobs and repairs and will adhere up to 40 tiles. It's economical, too – one can of TILE BOND is equivalent to more than seven tubes of caulk adhesive.

Why We Aren't Afraid of Hurricanes

TILE BOND™ Roof Tile Adhesive is Metro-Dade Approved and hurricane-proven. TILE BOND is approved for use in applications where 146 mph wind uplift resistance is required.*



Acceptance No.: 06.0417.02
Expires: 08/23/2011

Strength on Any Job

Whatever the project, TILE BOND™ Roof Tile Adhesive is ready to work. You can be assured of the strength of TILE BOND in any application.



Low/Flat Tile Profile



Medium Tile Profile



High Tile Profile



Two Piece Barrel Tile Profile

NOTE: TILE BOND paddy placement in photographs is for reference only.

For Technical Assistance, call or visit website:
• 1-888-583-BLUE(2583)
• www.dowstyrofoam.com/architect

Stick with Dow, where strength is a breeze.

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. Dow assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

COMBUSTIBLE: TILE BOND™ Roof Tile Adhesive should be stored away from heat sources. For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

TILE BOND™ Roof Tile Adhesive contains isocyanate, hydrofluorocarbon and polyol. Read the Material Safety Data Sheet carefully before use. Wear protective clothing, gloves and goggles and provide adequate ventilation and/or wear proper respiratory protection.

THE DOW CHEMICAL COMPANY • Building Solutions • 200 Larkin • Midland, MI 48674
FOR TECHNICAL INFORMATION: 1-866-583-BLUE (2583)
FOR SALES INFORMATION: 1-800-232-2436
www.dowstyrofoam.com/architect



a proud partner of

