

## Tile Roof Replacement Work Sheet

### Design Your Tile Roof

#### Deck Fastening (Choose One):

- 8d Ring Shank Nail 8-6-12
- 8d Ring Shank Nail 8-6-6
- 8d Ring Shank Nail 8-4-6

#### Deck Protection:

- #30lb. Felt Paper. Nailed
- #90lb. Felt Paper Applied with hot asphalt
- Polyester Surfaced Self-Adhered, direct to deck
- 30lb. Felt Paper Nailed
- Polyester Surfaced Self-Adhered
- Self-Adhered, direct to deck base with Polyester Surfaced Self-Adhered
- Stone-Coated Self-Adhered direct to deck

#### Existing Skylights:

- Reuse Existing
- Replace with Plastic Dome Skylight
- Replace with VELUX Impact Resistant Skylight
- I do not have an existing Skylight

#### Flashing:

- Reseal Existing Flashing
- New Exterior Flashing
- New Concealed Flashing

### Tile Options

#### Tile:

- Low Barrel, Concrete
- High Barrel, Concrete
- Flat 13", Concrete
- Flat 9", Concrete
- Spanish S, Concrete
- Spanish S, Concrete

#### Tile Attachment

- Mortar Only
- 1 Zinc Screw
- 2 Zinc Screws
- 1 Stainless Steel Screw
- 2 Stainless Steel Screws
- Tile Adhesive Only
- Tile Adhesive & 1 Stainless Steel Screw

#### Hip & Ridge

Mortar Edge Point Up Only

- Tile-Tite Full Mortar
- Wood Ridge Anchor, Zinc Screw, Mortar Edge
- Metal Ridge Anchor, Zinc Screw, Mortar Edge
- Metal Ridge Anchor, Zinc Screw, Tile Adhesive, Mortar Edge
- Metal Ridge Anchor, Stainless Steel Screw, Tile Adhesive, Mortar Edge